



Ji'nan ShengTai Painting Equipment Co.,Ltd.
Address: East of the intersection of Dongwaihuan Road and Wenhua Road in Wenden Village,
Diaozen Street, Zhangqiu District, Jinan City, Shandong Province
Email: ceces2018917@gmail.com WhatsApp:+8615854139190

Metal Parts Coating — Powered by ShengTai Model MPCL-SGK21

Schematic diagram of the spraying gun Within a powder coating line, the coating material is conveyed via the internal feed conduit of the spraying gun to guarantee an unwavering and consistent material flow, ensuring clog-free operation. The reliable and non-stop material delivery from this powder coating machine is essential for maintaining high productivity and finish quality.

Advantages:

1. Intelligent Digital Control — Easily adjust settings with the push of a button for highly accurate and consistent powder output.
2. Universal Compatibility — Achieve a flawless finish on all types of work-pieces with superior coating performance.
3. Sleek & Portable Design — Modern and compact, ideal for small-scale production and on-the-go operations.
4. User-Friendly Operation — Perfect for both beginners and advanced users, ensuring a smooth experience from start to finish.
5. Durable & Trusted — Built for long-lasting performance, this model is a popular choice for reliability and efficiency.

Model: MPCL-SGK21

Voltage: AC100 to 120V $\pm 10\%$; AC200 to 240V $\pm 10\%$

Dimension(l*w*h): 67CM*47CM*66CM

Weight (kg): 40

Power(w): 45W

Machine type: Coating Equipment

Operating Mode: Manual

Coating: Powder Coating

Substrate: Steel

Core components: PLC, Pump, controller

Machinery/Video: test report Not Available/ outgoing-inspection Provided

Place of origin: Shandong, China

Brand name: ShengTai



Ji'nan ShengTai Painting Equipment Co.,Ltd.
Address: East of the intersection of Dongwaihuan Road and Wenhua Road in Wenden Village,
Diaozen Street, Zhangqiu District, Jinan City, Shandong Province
Email: ceces2018917@gmail.com WhatsApp:+8615854139190

Product name: Manual Electrostatic Powder Coating Gun Machine

Application: Surface Treatment

Working current: Max 80 μ A

Polarity: Negative

Input air pressure: 0.15–0.8MPA

Warranty: 1 Year