Ji'nan ShengTai Painting Equipment Co.,Ltd.
Address: East of the intersection of Dongwaihuan Road and Wenhua Road in Wenden Village, Diaozhen Street, Zhangqiu District, Jinan City,Shandong Province
Email: ceces2018917@gmail.com WhatsApp:+8615854139190

Automated Electronically controlled reciprocators

ST-PCL-R150S

I. Parameters of Electronic Control

Input Voltage: AC220V

Input Frequency: 50Hz

Input Power/Current: 40W /1A

Output Voltage (Low) DC: 0～18V

Operating Temperature: -10～50°C

II. Spray Gun Parameters

Output Voltage: DC 0～100kV

Output Current: 150μA

Protection Level: IP54

Polarity: Negative

Cable Grabbing Length: 4M

Maximum Powder Output: 650 g/Min

III. Parameters of Pneumatic control unit

Voltage: DC24V

Input Air Pressure 6～8 bav

Air Flow Rate: Max 13 Nm^3/h

Water Content in Compressed Air: Max 1.3 g/Nm^3

Oil Content in Compressed Air: Max 0.01 g/Nm^3

IV. Parameters of Reciprocator

Dimensions: 670mm × 560mm × 2700mm

Stroke: 1500mm

Lifting rod load: 40KG

Speed range: Infinitely adjustable, 0~45 m/Min (corresponding to the assembly line 5 m/Min) Acceleration: 1 m/sec^2

Input voltage: AC220V 50HZ 5A

Rated power: 0.75 KW

Protection function: Upper and lower limit switch with cushion rubber buffer

Operating temperature: 60°C